By **Ryan Stacy**
Senior Director of Marketing & Product Management
ALKON CORPORATION

FLUID POWER JOURNAL
Published: September, 2026

KEEPING PRODUCTION MOVING

THE ROLE OF PNEUMATIC CYLINDER SELECTION IN PACKAGING OPERATIONS



Ryan Stacy
Senior Director of Marketing & Product Management

In packaging, automation, and food and beverage processing equipment, pneumatic cylinder problems rarely begin with a complete failure. More often, they show up as small changes in how the machine runs. A transfer loses smoothness. A stop needs adjustment more often. A timed sequence no longer operates with the same consistency it had at startup. A diverter gate starts sticking during production.

The line may continue to run, but stability is already slipping. In high-cycle systems, small inconsistencies can affect product handling, increase scrap, and leave operators spending more time correcting the machine than running it. By the time anyone calls it a cylinder problem, the cost has already started to accumulate. Cylinder selection plays a direct role in preventing that gradual decline. Bore and stroke define the basic dimensions, but long-term reliability depends on how well the cylinder fits the load, cycle rate, environment, and pneumatic system around it.



MATCH THE CYLINDER TO THE JOB

Pneumatic cylinders handle positioning, clamping, diverting, cutting, sealing, and transfer operations. All those motions rely on compressed air actuation, but each one places different demands on the cylinder. Load, duty cycle, mounting configuration, available space, and timing requirements all shape what dependable performance requires. As duty requirements increase, construction quality becomes more important. High-cycle operation is hard on seals and internal components, especially in applications where downtime is difficult to schedule.

Rebuildable cylinder designs extend service life by allowing maintenance teams to replace seals and other wear-prone components without replacing the full actuator. Many plants take that a step further by keeping spare cylinders available for immediate installation, then rebuilding pulled units off-line without holding up production. The initial investment is higher, but in the long run, rebuild kits can lower maintenance costs and make cylinder replacement less disruptive.

Space is another constraint. Compact machines often leave limited room for valves, tubing, and service access. When valves must be mounted farther from the actuator, longer air lines can slow response and add leak points. Integrated valve configurations

© Fluid Power Journal 2026

address that challenge by consolidating plumbing, simplifying installation, and improving response without increasing the machine footprint.

A standard pneumatic cylinder can be fast and consistent, but some applications require smoother, more controlled motion throughout the stroke. That control helps prevent abrupt movement, stabilize product handling, and improve machine timing without adding unnecessary complexity.

Food processing raises the bar even further. Washdown cycles, aggressive cleaning chemicals, moisture, and temperature swings require specialized designs that support product longevity in sanitary environments. Stainless steel construction, crevice-free surfaces, food-grade grease, and minimized exposed threads maintain performance under those conditions. Beyond performance, those features reduce areas where dangerous bacteria can collect, lowering the risk of foodborne illness, costly recalls, and lasting reputational damage.

WHERE RELIABILITY STARTS TO BREAK DOWN

Most cylinder problems develop gradually. The machine keeps cycling, but it takes more attention to keep it running well.

Contamination is a common cause. Packaging environments can expose cylinders to dust, film, debris, and adhesive buildup. Food processing environments add moisture, detergents, and product residue through routine washdown cycles. Over time, those conditions can break down lubrication, damage sealing surfaces, and weaken cylinder performance long before the actuator stops working altogether.

Misalignment exacerbates the problem. Without proper support from the machine structure or external guides, side loading can place uneven stress on the rod and bearing surfaces. That stress accelerates wear and leads to premature seal failure. Additionally, under-sizing is one of the most deceptive design flaws. A cylinder may perform well at startup, then struggle as cycle rates increase, friction builds, or plant air pressure varies during day-to-day production.

THE PNEUMATIC SYSTEM MATTERS TOO

Cylinder performance extends beyond the actuator itself. Valve response, air quality, pressure regulation, tubing, fittings, and flow control all play a role. The right supplier adds value by evaluating the cylinder, pneumatic system, and machine layout together. That broader view helps OEMs identify fit, response, and performance concerns before they reach production. When equipment is down, replacement parts are needed, or an application requires modification, domestic manufacturing makes a meaningful difference.

RELIABILITY IS DEFINED BEFORE PRODUCTION

When a cylinder starts to fail in production, the cost rarely stays contained. It shows up in scrap, unplanned maintenance, troubleshooting time, and lost production. The greater risk is what those failures do to customer confidence. End users remember machines that caused problems. They may not trace the failure back to a specific actuator, but they will associate the downtime, financial impact, and risk to their own operation with the OEM. That association can influence future purchasing decisions long after the immediate issue is resolved.

Cylinder selection is not a small detail buried inside the equipment. Choose a cylinder that supports the full application, not just the available space. Above all, choose one engineered to keep performing years after the machine leaves the OEM floor.

For more information contact:
Alkon Corporation
728 Graham Drive, Fremont, OH 43420
419-333-7000 • www.alkoncorp.com

© Fluid Power Journal 2026